



Make the switch

## 1 Gang 2A 3Pin Unswitched Socket - Moulded, White

Stock code: A2315



### General

Face plate finish:	moulded
Insert colour:	
Number of outlets:	1
Outboard rocker:	
Rocker finish:	white moulded
Security features:	
Security key type:	
Switched:	No
With indicator lamp:	No
With RCD:	

### Technical

Associated standards:	BS 546
Ambient operating temperature:	-5 to 40°C (24hour average not exceeding 25°C)
Base material:	Thermoset
Display:	
Earth type:	
Face plate material:	thermoset
Fault current rating (mA):	
Fixing screws:	2 x M3.5
Inductive Load:	
IP rating:	IP2X
Maximum installation altitude:	2000m
Minimum switch contact gap:	
Minimum wall box depth:	25
Nature of supply:	AC
Operational testing:	30000
Output voltage:	
Rated current:	2A
Rated frequency:	50-60Hz
Rated kA:	
Rated VA:	
Rated voltage:	220-250V
Rated watts:	
Switched poles:	
Terminal capacity:	3 x 2.5mm 3 x 4.0mm 2 x 6.0mm
Trip characteristics:	

Technical: +44 (0) 208 208 7414 Sales: +44 (0) 208 208 7419 E-mail: sales@contactum.co.uk