



Make the switch

## 1 Gang 10AX Momentary Switch - Moulded, White

Stock code: A2719



### General

Face plate finish:	moulded
Insert colour:	
Number of switches:	1
Print legend:	No Print
Rocker finish:	
Switching operation:	momentary
With indicator lamp:	No

### Technical

Associated standards:	BS EN 60669-1
Ambient operating temperature:	-5 to 40°C (24hour average not exceeding 25°C)
Base material:	Thermoset
Display:	
Earth type:	
Face plate material:	thermoset
Fault current rating (mA):	
Fixing screws:	2 x M3.5
Inductive load:	
IP rating:	IP2X
Maximum installation altitude :	2000m
Minimum switch contact gap :	3 mm
Minimum wall box depth :	16
Nature of supply:	AC
Operational testing :	30000
Output voltage:	
Rated current:	10AX
Rated frequency:	50-60Hz
Rated kA :	
Rated VA:	
Rated voltage:	220-250V
Rated watts:	
Switched poles:	1 pole
Terminal capacity :	3 x 1.0mm 3 x 1.5mm 1 x 2.5mm
Trip characteristics:	

Technical: +44 (0) 208 208 7414 Sales: +44 (0) 208 208 7419 E-mail: sales@contactum.co.uk